




easy
8619 918_919_940_945_946_947_950_951



CEILING CUT
Ø220



8619 919	11W.	1.100	100lm/W.	-	3.000
8619 918	10W.	1.100	110lm/W.	-	4.000
8619 940	21W.	2.000	95lm/W.	-	3.000
8619 945	19W.	2.000	105lm/W.	-	4.000
8619 947	32W.	3.000	94lm/W.	-	3.000
8619 946	29W.	3.000	103lm/W.	-	4.000
8619 919 RD	11W.	1.100	100lm/W.	-	3.000
8619 918 RD	10W.	1.100	100lm/W.	-	4.000
8619 940 RD	21W.	2.000	95lm/W.	-	3.000
8619 945 RD	19W.	2.000	105lm/W.	-	4.000
8619 951	43W.	2.700	65lm/W.	-	3.000
8619 950	41W.	2.700	75lm/W.	-	4.000
8619 901RGB	24W.	1.000	42lm/W.	-	3.000
code	module W	lm	efficiency	beam angle	°K




colores_colors



materiales_materials

aluminio inyectado
y acero
die cast aluminium
and steel



easy

8946



en la imagen_in the picture



| easy
8619 918_919_940_945_946_947_950_951



easy



8619

iSpot



5003

ilutrac



3011NK

en la imagen_on picture



| easy
8619 918_919_940_945_946_947_950_951

easy



8946



en la imagen_in the picture